

minecraft

- [systemd unit](#)
- [серваки](#)
- [МОДЫ](#)

systemd unit

```
root@v1:~# cat /etc/systemd/system/minecraft@.service
[Unit]
Description=Minecraft server %I
After=local-fs.target network.target

[Service]
WorkingDirectory=/home/ubuntu/%i
User=ubuntu
Group=ubuntu
Type=forking
# Run it as a non-root user in a specific directory

ExecStart=/usr/bin/screen -h 1024 -dmS minecraft ./minecraft_server.sh
# I like to keep my commandline to launch it in a separate file
# because sometimes I want to change it or launch it manually
# If it's in the WorkingDirectory, then we can use a relative path

# Send "stop" to the Minecraft server console
ExecStop=/usr/bin/screen -p 0 -S minecraft -X eval 'stuff \"stop\"\\015'
# Wait for the PID to die - otherwise it's killed after this command finishes!
ExecStop=/bin/bash -c "while ps -p $MAINPID > /dev/null; do /bin/sleep 1; done"
# Note that absolute paths for all executables are required!

[Install]
WantedBy=multi-user.target
```

???????

Paper: <https://papermc.io/>

Purpur: <https://github.com/PurpurMC/Purpur> <https://purpurmc.org/>

Оптимизация: <https://github.com/YouHaveTrouble/minecraft-optimization>

Forge+Bukkit: <https://github.com/lzzelAliz/Arclight>

Остальные форки: <https://rubukkit.org/threads/nemnogo-o-forkax-paper-i-ne-tolko.176425/>

Почему не стоит использовать серваки с плагинами и модами: <https://rubukkit.org/threads/ne-ispolzujte-magma-mohist-catserver-i-podobnye-jadra.185662/>

????

<https://4mforyou.com/blog/forged-vs-fabric-vs-quilt-kakoj-mod-zagruzchik-minecraft-vybrat/>