

termux

Конфиг с кнопками:

```
cat .termux/termux.properties
### After making changes and saving you need to run `termux-reload-settings`
### to update the terminal. All information here can also be found on the
### wiki: https://wiki.termux.com/wiki/Terminal\_Settings

#####
# General
#####

### Allow external applications to execute arbitrary commands within Termux.
### This potentially could be a security issue, so option is disabled by
### default. Uncomment to enable.
# allow-external-apps = true

### Default working directory that will be used when launching the app.
# default-working-directory = /data/data/com.termux/files/home

### Uncomment to disable toasts shown on terminal session change.
# disable-terminal-session-change-toast = true

### Uncomment to not show soft keyboard on application start.
# hide-soft-keyboard-on-startup = true

### Uncomment to let keyboard toggle button to enable or disable software
### keyboard instead of showing/hiding it.
# soft-keyboard-toggle-behaviour = enable/disable

### Adjust terminal scrollbar buffer. Max is 50000. May have negative
### impact on performance.
# terminal-transcript-rows = 2000

### Uncomment to use volume keys for adjusting volume and not for the
### extra keys functionality.
```

```
# volume-keys = volume

#####

# Fullscreen mode
#####

### Uncomment to let Termux start in full screen mode.
# fullscreen = true

### Uncomment to attempt workaround layout issues when running in
### full screen mode.
# use-fullscreen-workaround = true

#####

# Cursor
#####

### Cursor blink rate. Values 0, 100 - 2000.
# terminal-cursor-blink-rate = 0

### Cursor style: block, bar, underline.
# terminal-cursor-style = block

#####

# Extra keys
#####

### Settings for choosing which set of symbols to use for illustrating keys.
### Choose between default, arrows-only, arrows-all, all and none
# extra-keys-style = default

### Force capitalize all text in extra keys row button labels.
# extra-keys-text-all-caps = true

### Default extra-key configuration
# extra-keys = [[ESC, TAB, CTRL, ALT, {key: '-', popup: '|'}, DOWN, UP]]

### Two rows with more keys
# extra-keys = [['ESC','/','-','HOME','UP','END','PGUP'], \
#               ['TAB','CTRL','ALT','LEFT','DOWN','RIGHT','PGDN']]
```

Configuration with additional popup keys (swipe up from an extra key)

```
# extra-keys = [[ \
#   {key: ESC, popup: {macro: "CTRL f d", display: "tmux exit"}}, \
#   {key: CTRL, popup: {macro: "CTRL f BKSP", display: "tmux ←"}}, \
#   {key: ALT, popup: {macro: "CTRL f TAB", display: "tmux →"}}, \
#   {key: TAB, popup: {macro: "ALT a", display: "A-a"}}, \
#   {key: LEFT, popup: HOME}, \
#   {key: DOWN, popup: PGDN}, \
#   {key: UP, popup: PGUP}, \
#   {key: RIGHT, popup: END}, \
#   {macro: "ALT j", display: "A-j", popup: {macro: "ALT g", display: "A-g"}}, \
#   {key: KEYBOARD, popup: {macro: "CTRL d", display: "exit"}} \
# ]]
```

#####

Colors/themes

#####

Force black colors for drawer and dialogs

use-black-ui = true

#####

HW keyboard shortcuts

#####

Disable hardware keyboard shortcuts.

disable-hardware-keyboard-shortcuts = true

Open a new terminal with ctrl + t (volume down + t)

shortcut.create-session = ctrl + t

Go one session down with (for example) ctrl + 2

shortcut.next-session = ctrl + 2

Go one session up with (for example) ctrl + 1

shortcut.previous-session = ctrl + 1

Rename a session with (for example) ctrl + n

shortcut.rename-session = ctrl + n

```
#####
# Bell key
#####

### Vibrate device (default).
# bell-character = vibrate

### Beep with a sound.
# bell-character = beep

### Ignore bell character.
# bell-character = ignore

#####
# Back key
#####

### Send the Escape key.
# back-key=escape

### Hide keyboard or leave app (default).
# back-key=back

#####
# Keyboard issue workarounds
#####

### Letters might not appear until enter is pressed on Samsung devices
# enforce-char-based-input = true

### ctrl+space (for marking text in emacs) does not work on some devices
# ctrl-space-workaround = true

~ $
```

кнопочки в 2 ряда:

```
### Two rows with more keys
extra-keys = [['ESC','/','-','HOME','UP','END','PGUP','INS'], \
              ['TAB','CTRL','ALT','LEFT','DOWN','RIGHT','PGDN','DEL']]
```

Revision #2

Created 15 January 2024 19:44:43 by Ivan

Updated 15 January 2024 20:07:21 by Ivan